





Floors

ALUJET Groundfloor
For Parquet/Laminate



GF-02 ALUJET Groundfloor
With Heating




FL-01 ALUJET Attick
Floor/Ceiling




PDF ALUJET Floor Materials				
Material: Name	Material: Description	Material: URL	Material: Product Benefits	Material: Specification URL
Floor				
Floor Membrane ALUJET Floorjet Speed	Heat reflective floor membrane ALUJET Floorjet Speed 75m2 (1.5m x 50m)	https://lmshop.sk/product/alujet-bandchengewebe-1-03x100m-103m2/	ECO certificate; Heat-reflecting; Bitumen-free; Odour-neutral; Emission free; High tear strength; Extremely robust; Double-sided adhesive strip; Impervious to vapours; very flexible; no restoring forces; low weight; extremely fast installation because 1.50 m wide; Only scissors or cutter necessary for processing; according to DIN EN 13213 chap. 3.3.1.1. - Suitable for cavity floors.\	https://lmshop.sk/wp-content/uploads/2024/05/Floorjet-Speed-TD2406-EN.pdf
Floor Membrane ALUJET Sonic 3000	For parquet and laminate to reduce room and impact sound, 1x roll - 4.05m2 (750mm x 5.4m)	https://lmshop.sk/product/alujet-sonic-3000/	Suitable for underfloor heating; recyclable; free from PVC; bitumen free; creates a "warm, pleasant sound" in the room; no typical "laminate sound" (clack effect); excellent impact sound reduction (up to 36 dB) under laminate flooring; excellent room sound reduction of up to 26 sone under laminate flooring; steam protection and moisture protection against underground moisture; low installation height; very high pressure stability; especially suitable for click systems; high pressure stability = protection of the click system / click connection; very good heat conduction, consists of 80% natural rock-flour; resistant to aging; insensitive to moisture.	https://lmshop.sk/wp-content/uploads/2024/07/Sonic-3000-TD2428-EN.pdf
Membrane for warm floors ALUJET Bandchengewebe	Insulating material in the screed area and for laminating on floor heating insulating elements. Printed with a 50 x 50 mm grid. 103m2 (1.03m X100m)	https://lmshop.sk/product/alujet-bandchengewebe-1-03x100m-103m2/	Extremely tear-proof; with woven fabric inlay.	https://lmshop.sk/wp-content/uploads/2024/07/Bandchengewebe-TD1928-EN.pdf
Roof membrane 145g ALUJET Difujet BLU	ALUJET Difujet BLU is a 3-layer, diffusion-open formwork, and sarking membrane. It is the best basis for creating a temporary roof. Application area - For use on switched and unswitched roof constructions in pitched roofs, with and without full rafter insulation.	https://lmshop.sk/product/alujet-difujet-blutape-75m2/	Open to diffusion; suitable for 2 months as a temporary covering; 90°C temperature resistance; use of the highest-quality nonwovens; 3-layer nonwoven composite; fire behaviour E according to DIN EN 13501-1; slip-resistant; non-slip, also as an airtight layer under insulation, e.g. soft wood fibre boards; also under slate, shingles, fibre cement boards, metal coverings (except titanium zinc).	https://lmshop.sk/wp-content/uploads/2024/07/Difujet-BLU-TD2423-EN.pdf
Vapor barrier membrane 110g ALUJET Climajet SD Vario	Suited for use with injected thermal insulations. In order to further increase safety during installation, the ALUJET Climajet SD VARIO was equipped with UV stability. 75m2 (1.5m x 50m)	https://lmshop.sk/product/alujet-climajet-sd-vario-75m/	Active adjustment to climatic conditions; high level of protection and construction safety; Sd value moisture-variable from 0.25 to 25 m; high tear strength; especially suitable for injected thermal insulation; UV-resistance; with fabric insert; approval by the DIBt for standard compliant constructions according to DIN 68800-2 (wood protection standard).	https://lmshop.sk/wp-content/uploads/2024/05/Climajet-SD-VARIO-TD2303-EN.pdf
Vapor insulation membrane ALUJET Topjet	Vapor insulation membrane ALUJET Topjet 100m2 (4m x 25m)	https://lmshop.sk/product/alujet-topjet-4m-x-25m/	B2 according to DIN 4102; E according to DIN EN 13501-1; Sd-Value > 100 m; easy to use, high tear strength; low weight; meets the requirements of DIN 18234	https://lmshop.sk/wp-content/uploads/2024/05/Topjet-TD2349-EN.pdf

Walls


ALUJET Ventilated
External Wall



ALUJET External
Basement Wall




ALUJET Foundation
Wall



PDF ALUJET Wall Materials				
Material: Name	Material: Description	Material: URL	Material: Product Benefits	Material: Specification URL
Facade membrane 210g ALUJET Fassadenbahn + ALUJET Difutape Black 6cm X 25m	Facade membrane 210g ALUJET Fassadenbahn 75m2 (1.5m x 50m), For universal use on closed, semi-open or open ventilated facades. The membrane has no spacing restrictions. To fix use Permanent UV-resistant black adhesive tape for exterior use ALUJET Difutape Black 6cm X 25m	https://lmshop.sk/product/alujet-fassadenbahn-facades-membrana/	Without joint limitation; PES fleece with multiple coatings; UV-resistant; Permeable; Weather-resistant	https://lmshop.sk/wp-content/uploads/2024/05/Fassadenbahn-TD2413-EN.pdf
Floor membrane with adhesive ALUJET Floorjet Anschlussstreifen Speed	The ALUJET Anschlussstreifen SPEED is a 5-layer composite material that is adhesive across the whole surface for use as a system component for ALUJET Walljet ALU and ALUJET Floorjet Speed. 16.25m2 (500mm x 32.5m), 11.375m2 (350mm x 32.5m), 6.5m2 (200mm x 32.5m)	https://lmshop.sk/product/alujet-floorjet-anschlussstreifen-speed/	Bitumen-free; Free from PVC; Self-adhesive across the whole surface; Extremely high adhesive strength; High tack; slotted separating liner for 500mm version.	https://lmshop.sk/wp-content/uploads/2024/05/Anschlussstreifen-SPEED-TD2406-EN.pdf
Floor Membrane ALUJET Floorjet Speed	Heat reflective floor membrane ALUJET Floorjet Speed 75m2 (1.5m x 50m)	https://lmshop.sk/product/alujet-bandchengewebe-1-03x100m-103m2/	ECO certificate; Heat-reflecting; Bitumen-free; Odour-neutral; Emission free; High tear strength; Extremely robust; Double-sided adhesive strip; Impervious to vapours; very flexible; no restoring forces; low weight; extremely fast installation because 1.50 m wide; Only scissors or cutter necessary for processing; according to DIN EN 13213 chap. 3.3.1.1. - Suitable for cavity floors.\	https://lmshop.sk/wp-content/uploads/2024/05/Floorjet-Speed-TD2406-EN.pdf

Roofs


ALUJET Concrete
Warm Roof




ALUJET Warm Roof
With Metal Deck



ALUJET Concrete
Warm Roof FD



ALUJET Wood Truss
Roof



PDF ALUJET Roof Materials			
Material: Name	Material: URL	Material: Product Benefits	Material: Specification URL
Vapor insulation membrane ALUJET Topjet	https://lmshop.sk/product/alujet-topjet-4m-x-25m/	B2 according to DIN 4102; E according to DIN EN 13501-1; Sd-Value > 100 m; easy to use, high tear strength; low weight; meets the requirements of DIN 18234	https://lmshop.sk/wp-content/uploads/2024/05/Topjet-TD2349-EN.pdf
Vapor insulation membrane 138g ALUJET Optima FDSK	https://lmshop.sk/product/alujet-optima-fdsk-75m2/	Full-surface self-adhesive; high tear resistance; high cover width; fast processing of large areas as there are fewer cross joints; E according to EN 13501-1; calorific value <10,500 kJ/m ² ; vapour-tight (sd value >1,500 m), reduced fire load.	https://lmshop.sk/wp-content/uploads/2024/07/Optima-FDSK-TD2409-EN.pdf
Vapor insulation membrane ALUJET Topjet FD	https://lmshop.sk/product/alujet-topjet-fd-4m-x-25m/	Low fire load; E according to DIN EN 13501-1; B2 nach DIN 4102; Sd-Value ≥ 120 m; easy to use; meets the requirements of DIN 18234; low weight; high tear strength.	https://lmshop.sk/wp-content/uploads/2024/05/Topjet-FD-TD1930-EN.pdf
Vapor barrier membrane 110g ALUJET Climajet SD Vario	https://lmshop.sk/product/alujet-climajet-sd-vario-75m/	Active adjustment to climatic conditions; high level of protection and construction safety; Sd value moisture-variable from 0.25 to 25 m; high tear strength; especially suitable for injected thermal insulation; UV-resistance; with fabric insert; approval by the DIBt for standard compliant constructions according to DIN 68800-2 (wood protection standard).	https://lmshop.sk/wp-content/uploads/2024/05/Climajet-SD-VARIO-TD2303-EN.pdf
Roof membrane 270g ALUJET Master TPU	https://lmshop.sk/product/roof-membrane-270g-alujet-master-tpu-75m2-1-5m-x-50m/	Two waterproof layers; for the most extreme weather conditions; suitable for a rainproof roof underlay; non-slip when wet; extremely durable; 20-year ALUJET warranty***; 100°C permanent temperature resistance; processing from -5°C; 5 months UV-resistant; 16 weeks temporary covering; very high impact and abrasion resistance; extremely high tear resistance; meets the requirements of DIN 4426; very high bond adhesion.	https://lmshop.sk/wp-content/uploads/2025/02/ALUJET_GmbH_Master_TPU_DOP_Leistungserklaerung_LE10060.pdf